

SKID STEER LOADERS S650



S650 — SPECIFICATIONS

Machine Rating

Rated operating capacity (ISO 14397-1)	1282 kg
Tipping load (ISO 14397-1)	2564 kg
Pump capacity	87.10 L/min
Pump capacity (with high flow option)	115.50 L/min
System relief at quick couplers	23.8-24.5 MPa
Max. travel speed (high range - option)	19.8 km/h
Max. travel speed (low range)	11.4 km/h

Engine

Liigiiie		
Make / Model	Kubota / V3307-DI-TE3	
Fuel	Diesel	
Cooling	Liquid	
Power at 2400 RPM	55.4 kW	
Torque at 1425 RPM (SAE J1995 Gross)	264.0 Nm	
Number of cylinders	4	
Displacement	3331 cm ³	
Fuel tank	103.30 L	
Weights		
Operating weight	3777 kg	
Shipping weight	3540 kg	

Controls	
Vehicle steering	Direction and speed controlled by two hand levers
Loader hydraulics tilt and lift	Separate foot pedals, optional Advanced Control System
	(ACS), Advanced Hand Control (AHC) or Selectable
	Joystick Control (SJC)
Front auxiliary (standard)	Electrical switch on right-hand steering lever

Drive System

Transmission Infinitely variable tandem hydrostatic piston pumps, driving two fully reversing hydrostatic motors

Standard Features

High-back adjustable suspension seat	Lift arm support
Automatically activated glow plugs	Work lights, front and rear
Bob-Tach™ frame	Parking brake
Bobcat Interlock Control System (BICS)	Seat belt
Deluxe operator cab 1	Seat bar
Electrically activated proportional front auxiliary hydraulics	12 x 16.5, 12-ply, Heavy duty tyres
Engine/hydraulics system shutdown	Turbo-charger with approved spark arrestor
Instrumentation	Warranty: 12 months or 2000 hours (whichever occurs
	first)
4 Pall C - Pall all - Ola - L - (POPO) L	1100 0474 Fellis Okist Bertail (FORO)

Roll Over Protective Structure (ROPS) - meets requirements of SAE-J1040 and ISO 3471; Falling Object Protective Structure (FOPS) - meets requirements of SAE-J1043 and ISO 3449, Level I

Options


Two speed
High-Flow hydraulics
Deluxe instrument panel
Cab enclosure with heating
Air conditioning
Power Bob-Tach™
33 x 15.5-16.5, 12-ply, Superflota
12 v 16 5 12-ply Heavy duty tyre

tation tyres, offset rims 16.5, 12-ply, Heavy duty tyres, offset rims 12 x 16.5, 12-ply, Severe duty tyres

12 x 16.5, 12-ply, Severe duty tyres, poly filled

12 x 16.5, Solid flex tyres Advanced Control System (ACS) Advanced Hand Controls (AHC) Selectable Joystick Controls (SJC) Air ride seat with 2 point seat belt Air ride seat with 3 point seat belt Back-up alarm Beacon Fire extinguisher Strobe

Dimensions



(A)	4026.0 mm	(J)	3149.0 mm
(B)	2065.0 mm	(K)	800.0 mm
(C)	25.0°	(L)	42.0°
(D)	207.0 mm	(M)	97.0°
(E)	1150.0 mm	(N)	1880.0 mm
(F)	2754.0 mm	(O)	2106.0 mm
(G)	3474.0 mm	(P)	1507.0 mm
(H)	30.0°	(Q)	1832.0 mm
(1)	2447 0 mm		

Planers

Attachments

(l)

Angle Bro	oms
Augers	
Backhoes	
Bale Fork	3
Box Blade	s s
Breaker A	ccessories
Breakers	
Brushcat ^T	M Rotary Cutters
Brush Sav	VS
Bucket Ac	
	on Buckets
Concrete	
Concrete	
	on / Industrial
Buckets	
Diggers	
Dozer Bla	
Drop Ham	
Dumping	
	and Grain Buckets
Flail Cutte	
Forestry C	Cutters
Graders	
Grapples,	
Landplane	
Landscap	
Laser Equ	
Low Profil	
Miscellane	
Mixing Bu	ckets
Mowers	h I -
Packer W	
	k Accessories
	ks, Hydraulic

Pallet Forks. Standard

Rear Stabilizers Root Grapples Rotary Grinders Scarifiers Scrapers Seeders Silt Fence Installers Skeleton Buckets Snow & Light Material Buckets Snow Blades Snow Blowers Snow Pushers Snow V-Blades Sod Layers Soil Conditioners Spare Wheels Spreaders Steel Tracks Stump Grinders Sweepers Tillers Tilt-Tatch Tree Transplanters Trench Compactors Trenchers Utility Forks Utility Frames Vibratory Rollers Water Kits Wheel Saws Whisker Brooms Wood Chippers



Bobcat is a Doosan Company.

Doosan is a global leader in construction equipment, power & water solutions, engines, and engineering proudly serving customers and communities for more than a century. | Bobcat and the Bobcat logo are registered trademarks of Bobcat Company in the United States and various other countries.

©2017 Bobcat Company. All Rights Reserved.





